

Granular Potash 60% K₂O



North Plant

484 State Highway 243

Carlsbad, NM 88220

800.451.2888 :: Customer Service

PROPERTY	RANGE	TYPICAL	GUARANTEE
K ₂ O	60.0-60.8%	60.5%	60.0% min.
Moisture	0.05-0.25%	0.20%	
SGN		285	
UI		50	

PHYSICAL DATA, % CUMULATIVE

TYLER MESH	OPENING MM	TYPICAL % CUMULATIVE
+6	3.330	25
+8	2.360	82
+10	1.650	98
+14	1.170	99
+20	0.833	100

TYPICAL BULK DENSITY

67 lbs/ft³
1070 kg/m³

TYPICAL ANGLE OF REPOSE

28-32 degrees

TYPICAL CHEMICAL ANALYSIS %

KCl	95.7
K	50.2
Mg	0.07
Ca	0.1
Na	1.5
Cl	45.1
NaCl	3.5
SO ₄	0.3
Insoluble	0.3



The information shown in this data sheet represents average properties of product analyses of composite samples and typical analyses should not be considered a guaranteed specification. Individual shipment and grab sample analyses may fall outside of the above typical values due to natural variability within the product. Additional handling, transportation, or improper/extended storage may affect product analyses. Intrepid Potash disclaims any responsibility or liability for any loss or damage that may occur from any reliance on, or other use of, the above information with respect to the product.

Revised Date :: January 8, 2026

INTREPID

707 17th Street, Suite 4200, Denver, CO 80202

www.intrepidpotash.com

