INTREPID Potash®

MOAB

Granular Potash 60% K_2O

PROPERTY	RANGE	TYPICAL	GUARANTEE
K_2O	60.0-61.0%	60.5%	60.0% min.
Moisture	0.1-0.3%	0.10%	
SGN	280 - 310	290	
UI		45	

PARTICLE SIZE DISTRIBUTION

TYLER MESH	OPENING MM	TYPICAL % CUMULATIVE
+6	3.330	25
+8	2.360	75
+10	1.650	95
+14	1.170	98
+20	0.833	99

TYPICAL CHEMICAL ANALYSIS %

KCl	95.7
K	50.2
Mg	0.02
Ca	0.5
Na	1.0
Cl	47.0
NaCl	2.6
SO_4	0.9
Insoluble	0.06

TYPICAL BULK DENSITY

63 lbs/ft^3

1010 kg/m^3

TYPICAL ANGLE OF REPOSE

28-32 degrees

Intrepid Potash - Moab

Highway 279, Potash Road

Moab, UT 84532

800.451.2888 :: Customer Service

The information shown in this data sheet represents average properties of product analyses of composite samples and typical analyses should not be considered a guaranteed specification. Individual shipment and grab sample analyses may fall outside of the above typical values due to natural variability within the product. Additional handling, transportation, or improper/extended storage may affect product analyses. Intrepid Potash disclaims any responsibility or liability for any loss or damage that may occur from any reliance on, or other use of, the above information with respect to the product.

Revised Date :: January 8, 2026

INTREPID

707 17th Street, Suite 4200, Denver, CO 80202

www.intrepidpotash.com

INTREPID MADE & MANUFACTURED USA

INTREPID Essential Minerals for Success