

Feed Grade
Standard Potash 60% K₂O


Intrepid Potash - Moab

Highway 279, Potash Road

Moab, UT 84532

800.451.2888 :: Customer Service

PROPERTY	RANGE	TYPICAL	GUARANTEE
K ₂ O	60.0-61.0%	60.5%	60.0% min.
Moisture	0.1-0.3%	0.17%	
SGN		60	

PARTICLE SIZE DISTRIBUTION

TYLER MESH	OPENING MM	TYPICAL %	CUMULATIVE
+14	1.00	8	
+20	0.85	25	
+28	0.60	50	
+35	0.43	70	
+48	0.30	85	
+100	0.15	98	

TYPICAL BULK DENSITY

 70 lbs/ft³
 1120 kg/m³
TYPICAL ANGLE OF REPOSE
 28-32 degrees

TYPICAL CHEMICAL ANALYSIS %

KCl	95.7
K	50.1
Mg	0.02
Ca	0.4
Na	1.0
Cl	47.0
NaCl	2.6
SO ₄	0.9
Insoluble	0.2



The information shown in this data sheet represents average properties of product analyses of composite samples and typical analyses should not be considered a guaranteed specification. Individual shipment and grab sample analyses may fall outside of the above typical values due to natural variability within the product. Additional handling, transportation, or improper/extended storage may affect product analyses. Intrepid Potash disclaims any responsibility or liability for any loss or damage that may occur from any reliance on, or other use of, the above information with respect to the product.

Revised Date :: December 22, 2025

INTREPID

 707 17th Street, Suite 4200, Denver, CO 80202
www.intrepidpotash.com
