INTREPID Potash®

WENDOVER

Turf Grade Potash 230 SGN

PROPERTY	RANGE	TYPICAL	GUARANTEE
K_2O	60.0-61.0%	60.5%	60.0% min.
Moisture	0.1-0.3%	0.17%	
SGN	225-245	235	
UI		53	

PARTICLE SIZE DISTRIBUTION

TYLER MESH	OPENING MM	TYPICAL % CUMULATIVE
+6	3.35	2
+8	2.36	50
+10	1.70	91
+14	1.18	99
+20	0.85	99.5

TYPICAL BULK DENSITY

63 lbs/ft^3

1010 kg/m^3

TYPICAL ANGLE OF REPOSE

32 degrees

TYPICAL	CHEMICAL ANALYSIS %
KCl	95.9
K	50.3
Mg	0.1
Ca	0.07
Na	1.1
Cl	47.8
NaCl	2.8
SO_4	0.5
Insoluble	0.05

Intrepid Potash - Wendover

2 1/2 Miles East Frontage Road

Wendover, UT 84083

800.451.2888 :: Customer Service

The information shown in this data sheet represents average properties of product analyses of composite samples and typical analyses should not be considered a guaranteed specification. Individual shipment and grab sample analyses may fall outside of the above typical values due to natural variability within the product. Additional handling, transportation, or improper/extended storage may affect product analyses. Intrepid Potash disclaims any responsibility or liability for any loss or damage that may occur from any reliance on, or other use of, the above information with respect to the product.

Revised Date :: January 26. 2026

INTREPID

707 17th Street, Suite 4200, Denver, CO 80202

www.intrepidpotash.com

INTREPID MADE & MANUFACTURED USA

INTREPID Essential Minerals for Success