

Feed Grade Standard Potash 60% K₂O



Intrepid Potash-Moab

HWY. 279, Potash Road
Moab, Utah 84532

| PROPERTY | RANGE | TYPICAL | GUARANTEE |
|------------------|------------|---------|------------|
| K ₂ O | 60.0-61.0% | 60.5% | 60.0% min. |
| Moisture | 0.1-0.3% | 0.17% | |
| SGN | | 60 | |

PARTICLE SIZE DISTRIBUTION

| TYLER MESH | OPENING MM | TYPICAL % CUMULATIVE |
|------------|------------|----------------------|
| +14 | 1.00 | 8 |
| +20 | 0.85 | 25 |
| +28 | 0.60 | 50 |
| +35 | 0.43 | 70 |
| +48 | 0.30 | 85 |
| +100 | 0.15 | 98 |

TYPICAL BULK DENSITY

70 lbs/ft³
1120 kg/m³

TYPICAL ANGLE OF REPOSE

28-32 degrees

TYPICAL CHEMICAL ANALYSIS %

| | |
|-----------------|------|
| KCl | 95.7 |
| K | 50.1 |
| Mg | 0.02 |
| Ca | 0.4 |
| Na | 1.0 |
| Cl | 47.0 |
| NaCl | 2.6 |
| SO ₄ | 0.9 |
| Insoluble | 0.2 |



The information shown in this data sheet represents average properties of product analyses of composite samples and typical analyses should not be considered a guaranteed specification. Individual shipment and grab sample analyses may fall outside of the above typical values due to natural variability within the product. Additional handling, transportation, or improper/extended storage may affect product analyses. Intrepid Potash disclaims any responsibility or liability for any loss or damage that may occur from any reliance on, or other use of, the above information with respect to the product. **Revision Date :: 4/11/22**