



Feed Grade Standard Potash 60% K₂O



| PROPERTY | RANGE | TYPICAL | GUARANT |
|-------------------|------------|---------|---------|
| K ₂ O% | 60.0-61.0% | 60.5% | 60.0% m |
| Moisture% | 0.10-0.20% | 0.10% | |
| SGN | 35-55 | 45 | |
| | | | |

TEE nin.

PARTICLE SIZE DISTRIBUTION

| TYLER MESH | OPENING MM | TYPICAL % CUMULATIVE |
|------------|------------|----------------------|
| +14 | 1.00 | 3 |
| +20 | 0.85 | 15 |
| +28 | 0.60 | 35 |
| +35 | 0.43 | 43 |
| +48 | 0.30 | 68 |
| +100 | 0.15 | 89 |

TYPICAL BULK DENSITY

70 lbs/ft3 1120 kg/m³

TYPICAL ANGLE OF REPOSE

32 degrees



Intrepid Potash - Wendover

2 1/2 Miles E. Frontage Road Wendover, UT 84083

| +100 | 0.15 | | | |
|-----------------------------|------|--|--|--|
| TYPICAL CHEMICAL ANALYSIS % | | | | |
| KCI | 95.7 | | | |
| K | 50.2 | | | |
| Mg | 0.1 | | | |
| Ca | 0.07 | | | |
| Na | 1.2 | | | |
| Cl | 47.2 | | | |
| NaCl | 2.9 | | | |
| SO4 | 0.6 | | | |
| Insoluble | 0.05 | | | |





The information shown in this data sheet represents average properties of product analyses of composite samples and typical analyses should not be considered a guaranteed specification. Individual shipment and grab sample analyses may fall outside of the above typical values due to natural variability within the product. Additional handling, transportation, or improper/extended storage may affect product analyses. Intrepid Potash disclaims any responsibility or liability for any loss or damage that may occur from any reliance on, or other use of, the above information with respect to the product. Revision Date :: 4/11/22

707 17th Street, Suite 4200, Denver, CO 80202 www.intrepidpotash.com



